

From the makers of the **STOP IT® PIPE REPAIR SYSTEM**



20-MINUTE EPOXY

A hand-moldable, industrial strength, steel filled epoxy... stop leaks, fill holes and cracks, bond and repair almost anything.



No hot work or special tools required. Ready to use.


This simple, easy to use epoxy stick will stop leaks, fill holes and cracks fast. **FIX STIX™** sets rock hard in about 20 minutes, works underwater and in a wide temperature range. **FIX STIX™** is pre-measured, non-toxic, solvent free, has little odor, can be used on potable water lines and has excellent chemical resistance. It will not shrink, crack or pull away. **FIX STIX™** can be machined, threaded and painted after fully curing.



THOUSANDS OF USES!



Easy to use, super strength, saves money in repairs!



Fill holes, cracks and voids, repair threads, broken parts. Keep at least one in every toolbox.

FIX STIX™ – TECHNICAL INFORMATION

Physical Properties

Working time: 2 minutes

Set time: 20 minutes

Maximum use temperature: 300° F (149° C)

Dielectric strength: 300 volts/mil at 0.15 cm

Volume resistivity: 1×10^{12} ohm/cm

Density: 18.5 lb/gal (22gm/cm³)

Compression Strength: 12,000 psi

Tensile Strength: 6,000 psi

Modulus of Elasticity: 6×10^5 psi

Lap Shear Strength (steel): 900 psi

Izod Impact: 0.3 lb/in (notched)

Hardness (Shore D): 80

USDA: Acceptable for use in federally inspected meat and poultry plants

Ordering Information

Packaged: 28 units/case

Product Dimensions: 3.6" (9.2cm) x 7/8" (2.2cm) each unit

Case Dimensions: 12" x 9" x 5" (31cm x 23cm x 13cm)

Case Weight: 4.75 lbs (2kg)



Indumar Products, Inc.
P.O. Box 770008
Houston, TX 77215-0008
Phone 713.977.4100
1.800.523.STOP (7867)
Fax 713.977.4164
Email stopit@indumar.com
www.stopit.com